

SPECIFICATIONS

Standard	Top mounted handle. Adjustable thermostat.
Sealing Speed	Up to 400 inches per minute on lighter materials.
Sealing Capacity	Heavy MIL Spec material, heavy laminates and foils, plus cellophane and polyethylene when used with overcap labels.
Seal Impressions	Flat (Model F), Bead and Groove (Model G).
Seal Width	1".
Seal Length	Infinite (continuous).
Temperature Range	Adjustable from 200° through 550°F.

Electrical 115 Volts, 50/60 cycles, 1-phase AC. (Options available.)

Shipping Weight 7 lbs.

Shipping Dimensions 15"L x 6"W x 8"H.

OPTIONS (Up Charge)

- Side carrying handle for two-handed use.
- Conversion kit to change model F (flat seal) Sealer into a Model G (grooved seal) Sealer.
- Teflon* coating on preheater bars and pressure rolls (Model F only). Factory Approval.
- Electrical: 230 Volts, 50/60 cycles, 1-phase AC.



Form-Fit Handle has kink eliminator and strain relief for rubber covered cord with plug.

Adjustable Thermostat controls temperature from 200° through 500°F.

Pressure Roll Adjustment Knob to accommodate different materials and ensure a high quality seal.

Pilot Light indicates when desired sealing temperature as been reached.

Rounded Sealing Entrance facilitates feed of materials to help ensure a high quality seal with minimal effort.

Other Features:

- Frame casting, preheater bars, handle supports and rolls are all aluminum for light weight.
- Preheater bars (1" wide, 8-1/2" long) each have a 150-Watt, sheathed heating element for a total of 300 Watts.
- Sealer rolls of 1-1/2" diameter and 1" face run on ball bearings.
- All wiring is protected in the handle recess.

* Teflon is a registered trademark of Dupont.